## NSN 2010-00-352-0488

Ship Propulsion Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2010-00-352-0488 **Inside Diameter:** 10.875 inches Width: 1.875 inches **Overall Length:** 42.583 feet **Outside Diameter:** 16.000 inches **Taper Length:** 2.323 feet **Taper Major Diameter:** 18.750 inches **Keyway Width:** Between 2.125 inches and 2.187 inches **Keyway Depth:** 0.937 inches Depth: 0.875 inches **Keyway Quantity:** 3 and 1 **Surface Finish:** Smooth machined **Usage Design:** Sd445-451, 465-481, 498-502, 507-522, 526-541, 544-547, 550-597, 629-631, 642-644, 649, and dm23-34 **Unit Type:** Stern tube shaft section **Protective Covering Type:** Rubber **Construction:** Hollow **Usage Location:** Port/starboard Forward End Design: Tapered Forward End Keyway: Provided After End Keyway: Provided Forward End Taper Length:

Not included

**Threaded Forward End:** 

1.000 feet

## **NSN 2010-00-352-0488**Ship Propulsion Shaft - Page 2 of 2



After End Design:
Tapered
Threaded After End:
Not included
Forward Bearing Sleeve Outside Diameter:
17.375 inches
Forward Bearing Sleeve Length:
5.854 feet
After Bearing Sleeve Outside Diameter:
17.375 inches
After Bearing Sleeve Length:
5.500 feet
Covering Location:
Surfaces between bearing sleeve covered
Forward End Taper Major Diameter:
16.000 inches
Taper:
1.000 per foot in inches
Forward End Taper:
0.125 per foot in inches
Material:
Steel, n, 49-s-2, forged
Material:
Steel, n, 49-s-2, forged
Quantity:
2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T08000