

View Online at <https://aerobasegroup.com/nsn/2010-00-352-0490>

**Overall Length:**

27.438 feet

**Outside Diameter:**

8.750 inches

**Keyway Width:**

Between 1.125 inches and 1.187 inches

**Keyway Depth:**

0.531 inches

**Keyway Quantity:**

3 and 1

**Surface Finish:**

Smooth machined

**Coupling Outside Diameter:**

15.750 inches

**Usage Design:**

De51-113, 129-223, 234-255, 281-285, 316-424, 438-456, 508-511, 531-562, 567-616, 633-644, 665-723, 739-753, 763-774, 789-800, apd-37-40, 42-46-48-53, 55-57, 59-63, 65-67, 69-81, 84-136, 139

**Unit Type:**

Stern tube shaft section

**Protective Covering Type:**

Rubber

**Construction:**

Solid

**Usage Location:**

Port/starboard

**Forward End Design:**

Tapered

**Forward End Keyway:**

Provided

**After End Keyway:**

Not provided

**Forward End Taper Length:**

0.709 feet

**Threaded Forward End:**

Not included

**After End Coupling Design:**

Integral

**Coupling Thickness:**

1.750 inches

**Threaded After End:**

Not included

**Forward Bearing Sleeve Outside Diameter:**

9.687 inches

**Forward Bearing Sleeve Length:**

3.645 feet

**After Bearing Sleeve Outside Diameter:**

9.687 inches

**After Bearing Sleeve Length:**

4.490 feet

**Covering Location:**

Surfaces between bearing sleeve covered

**Forward End Taper Major Diameter:**

8.750 inches

**Forward End Taper:**

0.125 per foot in inches

**Material:**

Steel, mil, mil-s-890, forged

**Material:**

Steel, mil, mil-s-890, forged

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T08000