NSN 2010-00-352-0493

Ship Propulsion Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2010-00-352-0493

| Overall Length: |
|--|
| 17.427 feet |
| Outside Diameter: |
| 5.000 inches |
| Keyway Width: |
| Between 0.500 inches and 0.562 inches |
| Keyway Depth: |
| 0.250 inches |
| Keyway Quantity: |
| 3 and 1 |
| Surface Finish: |
| Smooth machined |
| Coupling Outside Diameter: |
| 11.000 inches |
| Unit Type: |
| Stern tube shaft section |
| Protective Covering Type: |
| Rubber |
| Construction: |
| Solid |
| Usage Location: |
| Port/starboard |
| Forward End Design: |
| Tapered |
| Forward End Keyway: |
| Provided |
| After End Keyway: |
| Not provided |
| Forward End Taper Length: |
| 0.375 feet |
| Threaded Forward End: |
| Not included |
| After End Coupling Design: |
| Integral |
| Coupling Length: |
| 0.209 feet |
| Coupling Thickness: |
| 1.250 inches |
| Threaded After End: |
| Not included |
| Forward Bearing Sleeve Outside Diameter: |
| 6.000 inches |

NSN 2010-00-352-0493Ship Propulsion Shaft - Page 2 of 2



| Forward Bearing Sleeve Length: |
|---|
| 3.104 feet |
| After Bearing Sleeve Outside Diameter: |
| 6.000 inches |
| After Bearing Sleeve Length: |
| 3.063 feet |
| Covering Location: |
| Surfaces between bearing sleeve |
| Forward End Taper Major Diameter: |
| 5.000 inches |
| Forward End Taper: |
| 0.125 per foot in inches |
| Material: |
| Steel, mil-s-890 |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-890 military specification single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| T08000 |
| Mil-std (military Standard): |
| Mil-s-890 spec. |
| |