

View Online at <https://aerobasegroup.com/nsn/2010-00-376-1484>

Major Diameter:

1.750 inches

Thread Length:

3.000 inches

Width:

0.625 inches

Overall Length:

11.188 feet

Outside Diameter:

2.500 inches

Taper Length:

0.604 feet

Taper Major Diameter:

2.500 inches

Keyway Width:

0.625 inches

Keyway Depth:

0.3125 inches

Depth:

0.3125 inches

Keyway Quantity:

1

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller nut, 1; propeller key, 1; coupling key, 1

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Solid

Thread Quantity:

5 per inch

Usage Location:

Port, starboard and center

Forward End Design:

Straight

Forward End Diameter:

2.500 inches

Forward End Keyway:

Provided

After End Keyway:

Provided

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

2.875 inches

Forward Bearing Sleeve Length:

0.490 feet

After Bearing Sleeve Outside Diameter:

3.000 inches

After Bearing Sleeve Length:

1.125 feet

Covering Location:

Surface between bearing sleeves

Taper:

0.750 per foot in inches

Material:

Steel, mil-s-890

Material:

Steel

Material Specification:

Mil-s-890 military specification single material response

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000

Mil-std (military Standard):

Mil-s-890 spec.