

View Online at <https://aerobasegroup.com/nsn/2010-00-376-1485>

Inside Diameter:

Between 3.000 inches and 9.500 inches

Major Diameter:

8.500 inches

Thread Length:

8.500 inches

Width:

2.500 inches

Overall Length:

40.406 feet

Outside Diameter:

14.375 inches

Taper Length:

2.958 feet

Taper Major Diameter:

14.375 inches

Depth:

1.063 inches

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Coupling bolt, 12; coupling nuts, 24; propeller key, 2; propeller nut, 1

Usage Design:

Lsd 28 to 31

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Keyway:

Not provided

After End Keyway:

Provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

24.750 inches

Forward End Coupling Length:

2.333 feet

Forward End Coupling Thickness:

2.875 inches

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

After Bearing Sleeve Outside Diameter:

15.625 inches

After Bearing Sleeve Length:

8.250 feet

Covering Location:

All exposed surfaces

Taper:

1.000 per foot in inches

Material:

Steel, mil, mil-s-890 class b-s, forged

Material:

Steel, mil, mil-s-890 class b-s, forged

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T08000