

View Online at <https://aerobasegroup.com/nsn/2010-00-391-9425>

**Inside Diameter:**

10.000 inches

**Major Diameter:**

17.000 inches

**Thread Length:**

13.750 inches

**Width:**

4.500 inches

**Overall Length:**

40.912 feet

**Outside Diameter:**

25.500 inches

**Taper Length:**

4.125 feet

**Taper Major Diameter:**

25.500 inches

**Keyway Width:**

3.000 inches

**Keyway Depth:**

1.000 inches

**Depth:**

1.625 inches

**Keyway Quantity:**

4

**Surface Finish:**

Smooth machined

**Furnished Items And Quantity:**

Propeller nut, 1; propeller key, 2; coupling keys, 4

**Unit Type:**

Propeller shaft section

**Protective Covering Type:**

Rubber

**Construction:**

Hollow

**Thread Quantity:**

4 per inch

**Usage Location:**

Port/starboard

**Forward End Design:**

Tapered

**Forward End Keyway:**

Provided

**After End Keyway:**

Provided

**Forward End Taper Length:**

20.250 feet

**Threaded Forward End:**

Not included

**After End Design:**

Tapered

**Threaded After End:**

Included

**Forward Bearing Sleeve Outside Diameter:**

27.750 inches

**Forward Bearing Sleeve Length:**

7.209 feet

**After Bearing Sleeve Outside Diameter:**

27.750 inches

**After Bearing Sleeve Length:**

10.917 feet

**Covering Location:**

Surfaces between bearing sleeves

**Forward End Taper Major Diameter:**

23.000 inches

**Taper:**

1.000 per foot in inches

**Forward End Taper:**

0.125 per foot in inches

**Material:**

Steel, mil-s-890

**Material:**

Steel

**Material Specification:**

Mil-s-890 military specification single material response

**Quantity:**

2

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T08000

**Mil-std (military Standard):**

Mil-s-890 spec.