## NSN 2010-00-396-3676

Ship Propulsion Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2010-00-396-3676 **Major Diameter:** 4.250 inches **Thread Length:** 4.125 inches Width: 1.500 inches **Overall Length:** 22.104 feet **Outside Diameter:** 5.750 inches **Taper Length:** 1.104 feet **Taper Major Diameter:** 5.750 inches **Keyway Width:** 1.000 inches **Keyway Depth:** 0.625 inches Depth: 0.500 inches **Keyway Quantity:** 2 **Surface Finish:** Smooth machined **Furnished Items And Quantity:** Propeller key, 1; propeller nut, 1 **Intermediate Bearing Sleeve Outside Diameter:** 6.625 inches **Intermediate Bearing Sleeve Length:** 2.167 feet **Unit Type:** Propeller shaft section **Construction:** Solid **Thread Quantity:** 3 per inch **Usage Location:** Port/starboard Forward End Design:

Forward End Keyway:

Tapered

Provided

## NSN 2010-00-396-3676

Ship Propulsion Shaft - Page 2 of 2



After End Keyway:
Provided
Forward End Taper Length:
0.583 feet
Threaded Forward End:
Included
Forward End Major Diameter:
4.000 inches
Forward End Thread Quantity:
3 per inch
Forward End Thread Length:
3.500 inches
After End Design:
Tapered
Threaded After End:
Included
Forward Bearing Sleeve Outside Diameter:
6.625 inches
Forward Bearing Sleeve Length:
3.167 feet
After Bearing Sleeve Outside Diameter:
6.625 inches
After Bearing Sleeve Length:
2.333 feet
Forward End Taper Major Diameter:
5.750 inches
Taper:
1.000 per foot in inches
Forward End Taper:
1.000 per foot in inches
Material:
Steel, mil-s-890, forged
Material:
Steel, mil-s-890, forged
Quantity:
1
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

T08000