

View Online at <https://aerobasegroup.com/nsn/2010-00-396-3676>

Major Diameter:

4.250 inches

Thread Length:

4.125 inches

Width:

1.500 inches

Overall Length:

22.104 feet

Outside Diameter:

5.750 inches

Taper Length:

1.104 feet

Taper Major Diameter:

5.750 inches

Keyway Width:

1.000 inches

Keyway Depth:

0.625 inches

Depth:

0.500 inches

Keyway Quantity:

2

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller key, 1; propeller nut, 1

Intermediate Bearing Sleeve Outside Diameter:

6.625 inches

Intermediate Bearing Sleeve Length:

2.167 feet

Unit Type:

Propeller shaft section

Construction:

Solid

Thread Quantity:

3 per inch

Usage Location:

Port/starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Taper Length:

0.583 feet

Threaded Forward End:

Included

Forward End Major Diameter:

4.000 inches

Forward End Thread Quantity:

3 per inch

Forward End Thread Length:

3.500 inches

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

6.625 inches

Forward Bearing Sleeve Length:

3.167 feet

After Bearing Sleeve Outside Diameter:

6.625 inches

After Bearing Sleeve Length:

2.333 feet

Forward End Taper Major Diameter:

5.750 inches

Taper:

1.000 per foot in inches

Forward End Taper:

1.000 per foot in inches

Material:

Steel, mil-s-890, forged

Material:

Steel, mil-s-890, forged

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000