

View Online at <https://aerobasegroup.com/nsn/2010-00-437-3358>

Major Diameter:

15.000 inches

Thread Length:

11.750 inches

Width:

5.000 inches

Overall Length:

50.854 feet

Outside Diameter:

28.250 inches

Taper Length:

4.417 feet

Taper Major Diameter:

30.125 inches

Depth:

2.812 inches

Surface Finish:

Smooth machined

Unit Type:

Propeller shaft section

Protective Covering Type:

Composition rust preventive

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Any acceptable

Forward End Design:

Straight

Forward End Diameter:

Between 28.312 inches and 28.314 inches

Forward End Keyway:

Not provided

After End Keyway:

Provided

Forward End Coupling Design:

Detachable

Forward End Coupling Type:

Flange

Forward End Coupling Outside Diameter:

Between 44.997 inches and 45.000 inches

Forward End Coupling Thickness:

5.750 inches

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

Between 30.115 inches and 30.125 inches

Forward Bearing Sleeve Length:

7.448 feet

After Bearing Sleeve Outside Diameter:

Between 30.115 inches and 30.125 inches

After Bearing Sleeve Length:

11.333 feet

Covering Location:

Bore

Taper:

0.500 per foot in inches

Material:

Steel, mil-s-23284, class 2

Material:

Steel, mil-s-23284, class 2

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T08000