

View Online at <https://aerobasegroup.com/nsn/2010-00-469-6768>

Inside Diameter:

9.000 inches

Major Diameter:

10.000 inches

Thread Length:

8.500 inches

Width:

Between 2.750 inches and 2.812 inches

Overall Length:

35.281 feet

Outside Diameter:

16.000 inches

Taper Length:

3.000 feet

Taper Major Diameter:

16.000 inches

Keyway Width:

Between 1.813 inches and 1.876 inches

Keyway Depth:

1.317 inches

Depth:

1.625 inches

Keyway Quantity:

3 and 1

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Coupling, 1; coupling keys, 4; propeller key, 2; propeller nut, 1; coupling studs, 12; coupling nuts, 24

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Center

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Coupling Design:

Detachable

Forward End Coupling Type:

Sleeve

Forward End Coupling Outside Diameter:

28.000 inches

Forward End Coupling Length:

1.375 feet

Forward End Coupling Thickness:

1.688 inches

Forward End Taper Length:

1.167 feet

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

17.375 inches

Forward Bearing Sleeve Length:

3.120 feet

After Bearing Sleeve Outside Diameter:

17.375 inches

After Bearing Sleeve Length:

6.250 feet

Covering Location:

Surfaces between bearing sleeves covered

Forward End Taper Major Diameter:

7.250 inches

Taper:

1.000 per foot in inches

Forward End Taper:

0.125 per foot in inches

Material:

Steel, mil-s-23284, cold rolled

Material:

Steel, mil-s-23284, cold rolled

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T08000