NSN 2010-00-529-9164

Ship Propulsion Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2010-00-529-9164

Inside Diameter:
4.187 inches
Overall Length:
32.838 feet
Outside Diameter:
6.755 inches
Surface Finish:
Smooth machined
Coupling Outside Diameter:
16.000 inches
Usage Design:
Suitable for ms0519 class
Unit Type:
Propeller shaft section
Construction:
Hollow
Forward End Keyway:
Not provided
After End Keyway:
Not provided
Forward End Coupling Design:
Integral
Integral
Integral Forward End Coupling Outside Diameter:
Integral Forward End Coupling Outside Diameter: 6.7515 inches
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness:
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End:
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included After End Coupling Design:
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included After End Coupling Design: Integral
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included After End Coupling Design: Integral Coupling Thickness:
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included After End Coupling Design: Integral Coupling Thickness: 1.875 inches
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included After End Coupling Design: Integral Coupling Thickness: 1.875 inches Threaded After End:
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included After End Coupling Design: Integral Coupling Thickness: 1.875 inches Threaded After End: Not included
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included After End Coupling Design: Integral Coupling Thickness: 1.875 inches Threaded After End: Not included Material:
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included After End Coupling Design: Integral Coupling Thickness: 1.875 inches Threaded After End: Not included Material: Aluminum bronze, mil, mil-b-15939, composition 2
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included After End Coupling Design: Integral Coupling Thickness: 1.875 inches Threaded After End: Not included Material: Aluminum bronze, mil, mil-b-15939, composition 2
Integral Forward End Coupling Outside Diameter: 6.7515 inches Forward End Coupling Thickness: 0.656 inches Threaded Forward End: Not included After End Coupling Design: Integral Coupling Thickness: 1.875 inches Threaded After End: Not included Material: Aluminum bronze, mil, mil-b-15939, composition 2

NSN 2010-00-529-9164

Ship Propulsion Shaft - Page 2 of 2

Demilitarization:

No

Fiig:

товооо

