

View Online at <https://aerobasegroup.com/nsn/2010-00-529-9731>

Major Diameter:

5.250 inches

Thread Length:

5.750 inches

Width:

2.000 inches

Overall Length:

27.875 feet

Outside Diameter:

9.063 inches

Taper Length:

19.250 feet

Taper Major Diameter:

9.063 inches

Keyway Width:

Between 1.125 inches and 1.188 inches

Keyway Depth:

0.500 inches

Depth:

0.875 inches

Keyway Quantity:

3 and 1

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller nut, 1; propeller key, 1

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Solid

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Taper Length:

6.520 feet

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

10.312 inches

Forward Bearing Sleeve Length:

4.510 feet

After Bearing Sleeve Outside Diameter:

10.312 inches

After Bearing Sleeve Length:

4.250 feet

Covering Location:

Surfaces between bearing sleeve covered

Forward End Taper Major Diameter:

8.940 inches

Taper:

1.000 per foot in inches

Forward End Taper:

0.125 per foot in inches

Material:

Steel, mil-s-890

Material:

Steel

Material Specification:

Mil-s-890 military specification single material response

Quantity:

1

Reference Number Differentiating Characteristics:

As differentiated by material, material specification/standard, forward bearing sleeve data, and after bearing sleeve data

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T08000

Mil-std (military Standard):

Mil-s-890 spec.