

View Online at <https://aerobasegroup.com/nsn/2010-00-540-8598>

Inside Diameter:

Between 7.000 inches and 14.250 inches

Overall Length:

54.333 feet

Outside Diameter:

20.750 inches

Keyway Width:

Between 3.500 inches and 3.562 inches

Keyway Depth:

1.312 inches

Keyway Quantity:

1 and 3

Surface Finish:

Smooth machined

Coupling Outside Diameter:

34.750 inches

Unit Type:

Stern tube shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Usage Location:

Port/starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Not provided

Forward End Taper Length:

1.542 feet

Threaded Forward End:

Not included

After End Coupling Design:

Integral

Coupling Thickness:

4.250 inches

Threaded After End:

Not included

Forward Bearing Sleeve Outside Diameter:

22.500 inches

Forward Bearing Sleeve Length:

2.479 feet

After Bearing Sleeve Outside Diameter:

22.500 inches

After Bearing Sleeve Length:

6.000 feet

Covering Location:

Surfaces between bearing sleeves and surface between bearing sleeve and coupling covered

Forward End Taper Major Diameter:

19.000 inches

Forward End Taper:

0.125 per foot in inches

Material:

Steel, mil-s-890, class an

Material:

Steel

Material Specification:

Mil-s-890, class an military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T08000

Mil-std (military Standard):

Mil-s-890 spec.