

View Online at <https://aerobasegroup.com/nsn/2010-00-540-8599>

Inside Diameter:

Between 5.375 inches and 14.250 inches

Major Diameter:

12.500 inches

Thread Length:

11.375 inches

Width:

Between 3.250 inches and 3.313 inches

Overall Length:

49.406 feet

Outside Diameter:

20.750 inches

Taper Length:

4.073 feet

Taper Major Diameter:

20.750 inches

Depth:

1.250 inches

Surface Finish:

Smooth machined

Usage Design:

Suitable for dlg 6-15

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Keyway:

Not provided

After End Keyway:

Provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

34.750 inches

Forward End Coupling Length:

0.709 feet

Forward End Coupling Thickness:

4.250 inches

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

22.500 inches

Forward Bearing Sleeve Length:

5.708 feet

After Bearing Sleeve Outside Diameter:

22.500 inches

After Bearing Sleeve Length:

7.719 feet

Covering Location:

Surfaces between bearing sleeves covered

Taper:

1.000 per foot in inches

Special Features:

Shaft is cold rolled for a distance of 12 ft 9-3/4 in. Starting at the aft end of the propeller taper

Material:

Steel, mil-s-890, class an

Material:

Steel

Material Specification:

Mil-s-890, class an military specification single material response

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T08000

Mil-std (military Standard):

Mil-s-890 spec.