

View Online at <https://aerobasegroup.com/nsn/2010-00-541-0110>

**Inside Diameter:**

Between 3.500 inches and 7.000 inches

**Major Diameter:**

8.000 inches

**Thread Length:**

7.625 inches

**Width:**

Between 2.375 inches and 2.438 inches

**Overall Length:**

2.481 feet

**Outside Diameter:**

12.533 inches

**Taper Length:**

1.959 feet

**Taper Major Diameter:**

12.500 inches

**Keyway Width:**

Between 1.500 inches and 1.562 inches

**Keyway Depth:**

0.750 inches

**Depth:**

1.000 inches

**Keyway Quantity:**

3 and 1

**Surface Finish:**

Smooth machined

**Furnished Items And Quantity:**

Propeller nut 1; propeller key, 2

**Unit Type:**

Propeller shaft section

**Protective Covering Type:**

Rubber

**Construction:**

Hollow

**Thread Quantity:**

4 per inch

**Usage Location:**

Center

**Forward End Design:**

Tapered

**Forward End Keyway:**

Provided

**After End Keyway:**

Provided

**Forward End Taper Length:**

1.258 feet

**Threaded Forward End:**

Not included

**After End Design:**

Tapered

**Threaded After End:**

Included

**Forward Bearing Sleeve Outside Diameter:**

13.625 inches

**Forward Bearing Sleeve Length:**

4.583 feet

**After Bearing Sleeve Outside Diameter:**

13.625 inches

**After Bearing Sleeve Length:**

6.500 feet

**Covering Location:**

Surfaces between bearing sleeves covered

**Forward End Taper Major Diameter:**

13.500 inches

**Taper:**

1.000 per foot in inches

**Forward End Taper:**

0.125 per foot in inches

**Special Features:**

Shaft is cold rolled in propeller taper area 9 ft 4-3/4 in. Lg starting 2 in. Forward of the after taper and extending 12 in. Beyond forward end of after sleeve

**Material:**

Steel, mil-s-890, forged

**Material:**

Steel, mil-s-890, forged

**Quantity:**

2

**Reference Number Differentiating Characteristics:**

As differentiated by special, features

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T08000