

View Online at <https://aerobasegroup.com/nsn/2010-00-573-8053>

**Inside Diameter:**

Between 13.380 inches and 13.560 inches

**Overall Length:**

30.088 feet

**Outside Diameter:**

Between 20.500 inches and 20.550 inches

**Diameter:**

Between 20.500 inches and 20.550 inches

**Surface Finish:**

Ground or rough machined or smooth machined

**Coupling Outside Diameter:**

35.500 inches

**Unit Type:**

Line shaft section

**Protective Covering Type:**

Composition rust preventive

**Construction:**

Hollow

**Usage Location:**

Port

**Forward End Design:**

Straight

**Forward End Diameter:**

Between 20.500 inches and 20.550 inches

**Forward End Keyway:**

Not provided

**After End Keyway:**

Not provided

**Forward End Coupling Design:**

Integral

**Forward End Coupling Outside Diameter:**

35.500 inches

**Forward End Coupling Length:**

0.442 feet

**Forward End Coupling Thickness:**

4.250 inches

**Threaded Forward End:**

Not included

**After End Coupling Design:**

Integral

**Coupling Length:**

0.354 feet

**Coupling Thickness:**

4.250 inches

**After End Design:**

Straight

**Threaded After End:**

Not included

**Forward Bearing Sleeve Outside Diameter:**

Between 20.621 inches and 20.625 inches

**Forward Bearing Sleeve Length:**

2.250 feet

**After Bearing Sleeve Outside Diameter:**

Between 20.621 inches and 20.625 inches

**After Bearing Sleeve Length:**

1.000 feet

**Covering Location:**

Surfaces between bearing sleeves and flange faces, bore surfaces

**Material:**

Steel, mil-s-23284, class 3

**Material:**

Steel, mil-s-23284, class 3

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T08000