

View Online at <https://aerobasegroup.com/nsn/2010-00-583-0275>

Inside Diameter:

Between 13.380 inches and 13.560 inches

Overall Length:

28.838 feet

Outside Diameter:

Between 20.500 inches and 20.550 inches

Diameter:

Between 20.500 inches and 20.550 inches

Surface Finish:

Ground or rough machined or smooth machined

Coupling Outside Diameter:

37.250 inches

Intermediate Bearing Sleeve Outside Diameter:

Between 20.621 inches and 20.625 inches

Intermediate Bearing Sleeve Length:

3.833 feet

Unit Type:

Stub shaft

Protective Covering Type:

Composition rust preventive

Construction:

Hollow

Usage Location:

Port/starboard

Forward End Design:

Straight

Forward End Diameter:

Between 20.500 inches and 20.550 inches

Forward End Keyway:

Not provided

After End Keyway:

Not provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

35.500 inches

Forward End Coupling Length:

0.442 feet

Forward End Coupling Thickness:

4.250 inches

Threaded Forward End:

Not included

After End Coupling Design:

Integral

Coupling Length:

0.375 feet

Coupling Thickness:

4.500 inches

After End Design:

Straight

Threaded After End:

Not included

Covering Location:

Surfaces between bearing sleeves and flangefaces, bore surfaces

Material:

Steel, mil-s-23284, class 3

Material:

Steel, mil-s-23284, class 3

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000