## NSN 2010-00-678-0416

Ship Propulsion Shaft - Page 1 of 2

Inside Diameter:



View Online at https://aerobasegroup.com/nsn/2010-00-678-0416

Between 7.000 inches and 12.000 inches
Overall Length:
42.359 feet
Outside Diameter:
18.500 inches
Keyway Width:
Between 3.250 inches and 3.312 inches
Keyway Depth:
1.400 inches
Keyway Quantity:
3 and 1
Surface Finish:
Smooth machined
Coupling Outside Diameter:
30.625 inches
Furnished Items And Quantity:
Coupling nuts and bolts, 12; plugs, 2
Unit Type:
Stern tube shaft section
Protective Covering Type:
Rubber
Construction:
Hollow
Usage Location:
Port/starboard
Forward End Design:
Tapered
Forward End Keyway:
Provided
After End Keyway:
Provided
Forward End Taper Length:
1.542 feet
Threaded Forward End:
Not included
After End Coupling Design:
Integral
Coupling Type:
Any acceptable
Coupling Thickness:

3.750 inches

## **NSN 2010-00-678-0416**Ship Propulsion Shaft - Page 2 of 2



Threaded After End:
Not included
Forward Bearing Sleeve Outside Diameter:
20.250 inches
Forward Bearing Sleeve Length:
3.500 feet
After Bearing Sleeve Outside Diameter:
20.250 inches
After Bearing Sleeve Length:
4.500 feet
Covering Location:
Surfaces between bearing sleeves covered
Forward End Taper Major Diameter:
17.7497 inches
Forward End Taper:
0.125 per foot in inches
Material:
Steel, mil, mil-s-890, class an, forged
Material:
Steel, mil, mil-s-890, class an, forged
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
Г08000