

View Online at <https://aerobasegroup.com/nsn/2010-00-721-5324>

**Inside Diameter:**

Between 4.250 inches and 11.250 inches

**Major Diameter:**

9.000 inches

**Thread Length:**

8.500 inches

**Width:**

1.875 inches

**Overall Length:**

52.281 feet

**Outside Diameter:**

16.500 inches

**Taper Length:**

4.125 feet

**Taper Major Diameter:**

16.500 inches

**Keyway Width:**

1.875 inches

**Keyway Depth:**

0.875 inches

**Depth:**

0.875 inches

**Keyway Quantity:**

2

**Surface Finish:**

Smooth machined

**Furnished Items And Quantity:**

Propeller nut, 1; propeller key, 2

**Usage Design:**

Suitable for dd692 class

**Unit Type:**

Propeller shaft section

**Protective Covering Type:**

Rubber

**Construction:**

Hollow

**Thread Quantity:**

4 per inch

**Usage Location:**

Port/starboard

**Forward End Design:**

Tapered

**Forward End Keyway:**

Provided

**After End Keyway:**

Provided

**Forward End Taper Length:**

2.323 feet

**Threaded Forward End:**

Not included

**After End Design:**

Tapered

**Threaded After End:**

Included

**Forward Bearing Sleeve Outside Diameter:**

18.000 inches

**Forward Bearing Sleeve Length:**

5.417 feet

**After Bearing Sleeve Outside Diameter:**

18.000 inches

**After Bearing Sleeve Length:**

7.364 feet

**Covering Location:**

All exposed surfaces covered

**Forward End Taper Major Diameter:**

18.750 inches

**Taper:**

1.000 per foot in inches

**Forward End Taper:**

1.000 per foot in inches

**Special Features:**

Cold rolled in propeller taper and after end of sleeve area

**Material:**

Steel, mil-s-890, class an

**Material:**

Steel

**Material Specification:**

Mil-s-890, class an military specification single material response

**Quantity:**

2

**Reference Number Differentiating Characteristics:**

Cptf, cptg, cpth, cptp, feat, and w/o protection rings, pc 107 and 108

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T08000

**Mil-std (military Standard):**

Mil-s-890 spec.