

View Online at <https://aerobasegroup.com/nsn/2010-00-725-6166>

Major Diameter:

17.500 inches

Thread Length:

15.000 inches

Width:

Between 5.600 inches and 5.601 inches

Overall Length:

34.188 feet

Outside Diameter:

26.000 inches

Taper Length:

3.417 feet

Taper Major Diameter:

26.000 inches

Keyway Width:

Between 6.626 inches and 6.627 inches

Keyway Depth:

2.524 inches

Depth:

2.187 inches

Keyway Quantity:

3 and 1

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller key, 2; propeller nut, 1

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Solid

Thread Quantity:

4 per inch

Usage Location:

Center

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Coupling Design:

Detachable

Forward End Coupling Type:

Flange

Forward End Coupling Outside Diameter:

36.500 inches

Forward End Coupling Length:

1.604 feet

Forward End Coupling Thickness:

2.250 inches

Forward End Taper Length:

1.459 feet

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

27.875 inches

Forward Bearing Sleeve Length:

6.333 feet

After Bearing Sleeve Outside Diameter:

27.875 inches

After Bearing Sleeve Length:

10.417 feet

Covering Location:

Surfaces between bearing sleeves

Forward End Taper Major Diameter:

21.500 inches

Taper:

1.000 per foot in inches

Forward End Taper:

0.125 per foot in inches

Material:

Steel, n, mil-s-890, class b, forged

Material:

Steel, n, mil-s-890, class b, forged

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T08000