

View Online at <https://aerobasegroup.com/nsn/2010-00-726-1077>

Inside Diameter:

Between 6.000 inches and 16.000 inches

Major Diameter:

15.250 inches

Thread Length:

13.500 inches

Width:

Between 3.000 inches and 3.062 inches

Overall Length:

66.667 feet

Outside Diameter:

24.000 inches

Taper Length:

4.875 feet

Taper Major Diameter:

24.000 inches

Depth:

Between 1.357 inches and 1.362 inches

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller nut, 1; propeller key, 2

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Port or starboard

Forward End Keyway:

Not provided

After End Keyway:

Provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

38.500 inches

Forward End Coupling Length:

0.792 feet

Forward End Coupling Thickness:

4.750 inches

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

25.875 inches

Forward Bearing Sleeve Length:

9.500 feet

After Bearing Sleeve Outside Diameter:

25.875 inches

After Bearing Sleeve Length:

13.083 feet

Covering Location:

All exposed surfaces

Taper:

1.000 per foot in inches

Material:

Steel, mil-s-890 cl an, forged

Material:

Steel, mil-s-890 cl an, forged

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T08000