

View Online at <https://aerobasegroup.com/nsn/2010-00-726-3683>

Inside Diameter:

Between 5.750 inches and 14.500 inches

Major Diameter:

15.250 inches

Thread Length:

13.250 inches

Width:

Between 3.750 inches and 3.812 inches

Overall Length:

43.667 feet

Outside Diameter:

22.250 inches

Taper Length:

3.604 feet

Taper Major Diameter:

22.250 inches

Depth:

1.742 inches

Surface Finish:

Smooth machined

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber, synthetic

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Center

Forward End Keyway:

Not provided

After End Keyway:

Provided

Forward End Coupling Design:

Integral

Forward End Coupling Type:

Flange

Forward End Coupling Outside Diameter:

35.375 inches

Forward End Coupling Length:

0.750 feet

Forward End Coupling Thickness:

4.500 inches

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

24.500 inches

Forward Bearing Sleeve Length:

1.000 feet

After Bearing Sleeve Outside Diameter:

24.500 inches

After Bearing Sleeve Length:

7.698 feet

Covering Location:

Surfaces between bearing sleeve

Taper:

1.000 per foot in inches

Material:

Steel, mil, mil-s-890, cl an, w/o nickel amend. 4, forged

Material:

Steel, mil, mil-s-890, cl an, w/o nickel amend. 4, forged

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T08000