

View Online at <https://aerobasegroup.com/nsn/2010-00-804-2693>

Major Diameter:

3.250 inches

Thread Length:

4.000 inches

Width:

1.500 inches

Overall Length:

18.459 feet

Outside Diameter:

5.625 inches

Taper Length:

1.145 feet

Taper Major Diameter:

5.625 inches

Keyway Width:

1.500 inches

Keyway Depth:

0.468 inches

Depth:

0.468 inches

Keyway Quantity:

2

Surface Finish:

Per dwgst1978-s4301-1419496tc finished shaft surface

Furnished Items And Quantity:

Propeller key, 1, propeller nut, 1, keeper nut, 1, coupling key, 1, fitted hex head bolts and hex nuts, 1.125 in. By 3.000 in. Lg, 4, fitted hex head bolts and hex nuts, 1.125 in. By 3.500in. Lg, 6, forward and aft bearing liner cast bronze

Unit Type:

Propeller shaft section

Construction:

Solid

Thread Quantity:

8 per inch

Usage Location:

Center

Forward End Design:

Straight

Forward End Diameter:

5.000 inches

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Coupling Design:

Detachable

Forward End Coupling Type:

Flange

Forward End Coupling Outside Diameter:

15.500 inches

Forward End Coupling Length:

0.792 feet

Forward End Coupling Thickness:

3.250 inches

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Taper:

1.000 per foot in inches

Material:

Bronze, nickel-aluminum, mil-b-15939, comp 2

Material:

Bronze, nickel-aluminum, mil-b-15939, comp 2

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000