

View Online at <https://aerobasegroup.com/nsn/2010-00-807-7986>

**Major Diameter:**

2.500 inches

**Thread Length:**

4.000 inches

**Width:**

0.750 inches

**Overall Length:**

10.927 feet

**Outside Diameter:**

3.375 inches

**Taper Length:**

0.812 feet

**Taper Major Diameter:**

3.375 inches

**Keyway Width:**

0.750 inches

**Keyway Depth:**

0.375 inches

**Depth:**

0.313 inches

**Keyway Quantity:**

1

**Surface Finish:**

Smooth machined

**Furnished Items And Quantity:**

Propeller key, 1

**Unit Type:**

Propeller shaft section

**Protective Covering Type:**

Rubber

**Construction:**

Solid

**Thread Quantity:**

4 per inch

**Usage Location:**

Center

**Forward End Design:**

Tapered

**Forward End Keyway:**

Provided

**After End Keyway:**

Provided

**Forward End Taper Length:**

0.375 feet

**Threaded Forward End:**

Included

**Forward End Major Diameter:**

2.500 inches

**Forward End Thread Quantity:**

4 per inch

**Forward End Thread Length:**

2.750 inches

**After End Design:**

Tapered

**Threaded After End:**

Included

**Forward Bearing Sleeve Outside Diameter:**

4.000 inches

**Forward Bearing Sleeve Length:**

1.042 feet

**After Bearing Sleeve Outside Diameter:**

4.000 inches

**After Bearing Sleeve Length:**

1.438 feet

**Covering Location:**

Surface between bearing sleeve covered in accordance w/mil-r-15058f, type 3

**Forward End Taper Major Diameter:**

3.375 inches

**Taper:**

0.750 per foot in inches

**Forward End Taper:**

0.750 per foot in inches

**Special Features:**

Shaft sleeves to conform w/fed specification qq-l-225 composition 5, centrifugal cast

**Material:**

Steel, abs, grade 2, forge

**Material:**

Steel, abs, grade 2, forge

**Quantity:**

1

**Reference Number Differentiating Characteristics:**

As differentiated by protective covering data and special features

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T08000