

View Online at <https://aerobasegroup.com/nsn/2010-00-807-7986>

Major Diameter:

2.500 inches

Thread Length:

4.000 inches

Width:

0.750 inches

Overall Length:

10.927 feet

Outside Diameter:

3.375 inches

Taper Length:

0.812 feet

Taper Major Diameter:

3.375 inches

Keyway Width:

0.750 inches

Keyway Depth:

0.375 inches

Depth:

0.313 inches

Keyway Quantity:

1

Surface Finish:

Smooth machined

Furnished Items And Quantity:

Propeller key, 1

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Solid

Thread Quantity:

4 per inch

Usage Location:

Center

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Taper Length:

0.375 feet

Threaded Forward End:

Included

Forward End Major Diameter:

2.500 inches

Forward End Thread Quantity:

4 per inch

Forward End Thread Length:

2.750 inches

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

4.000 inches

Forward Bearing Sleeve Length:

1.042 feet

After Bearing Sleeve Outside Diameter:

4.000 inches

After Bearing Sleeve Length:

1.438 feet

Covering Location:

Surface between bearing sleeve covered in accordance w/mil-r-15058f, type 3

Forward End Taper Major Diameter:

3.375 inches

Taper:

0.750 per foot in inches

Forward End Taper:

0.750 per foot in inches

Special Features:

Shaft sleeves to conform w/fed specification qq-l-225 composition 5, centrifugal cast

Material:

Steel, abs, grade 2, forge

Material:

Steel, abs, grade 2, forge

Quantity:

1

Reference Number Differentiating Characteristics:

As differentiated by protective covering data and special features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T08000