

View Online at <https://aerobasegroup.com/nsn/2010-00-814-8610>

**Inside Diameter:**

Between 4.500 inches and 9.000 inches

**Major Diameter:**

10.000 inches

**Thread Length:**

9.500 inches

**Width:**

Between 2.750 inches and 2.751 inches

**Overall Length:**

39.786 feet

**Outside Diameter:**

Between 16.000 inches and 16.006 inches

**Taper Length:**

3.000 feet

**Taper Major Diameter:**

16.000 inches

**Keyway Width:**

Between 1.812 inches and 1.813 inches

**Keyway Depth:**

1.317 inches

**Depth:**

1.625 inches

**Keyway Quantity:**

3 and 1

**Surface Finish:**

Smooth machined

**Furnished Items And Quantity:**

Propeller nut, 1; propeller key, 2

**Unit Type:**

Propeller shaft section

**Protective Covering Type:**

Rubber

**Construction:**

Hollow

**Thread Quantity:**

4 per inch

**Usage Location:**

Center

**Forward End Design:**

Tapered

**Forward End Keyway:**

Provided

**After End Keyway:**

Provided

**Forward End Taper Length:**

1.167 feet

**Threaded Forward End:**

Not included

**After End Design:**

Tapered

**Threaded After End:**

Included

**Forward Bearing Sleeve Outside Diameter:**

Between 17.371 inches and 17.375 inches

**Forward Bearing Sleeve Length:**

6.583 feet

**After Bearing Sleeve Outside Diameter:**

Between 17.371 inches and 17.375 inches

**After Bearing Sleeve Length:**

6.250 feet

**Covering Location:**

Surfaces between bearing sleeves covered

**Forward End Taper Major Diameter:**

17.250 inches

**Taper:**

1.000 per foot in inches

**Forward End Taper:**

0.125 per foot in inches

**Material:**

Steel, mil-s-890, class an

**Material:**

Steel

**Material Specification:**

Mil-s-890, class an military specification single material response

**Quantity:**

2

**Reference Number Differentiating Characteristics:**

Elrn dwg no. Ssb/n/608-203-1955601 and ssb/n/608-203-1955602, w/o epoxy resin insert, coupling, and coupling keys

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T08000

**Mil-std (military Standard):**

Mil-s-890 spec.