

View Online at <https://aerobasegroup.com/nsn/2010-00-938-2727>

Cylinder Quantity:

6 or 8

Assembly Form:

Partial

Strokes Per Cycle:

2 or 4

Starting Method:

Hydraulic cranking

Reduction Gear Ratio:

Any acceptable

Cooling Type:

Heat exchanger

Mounting Crossbeams:

Not included

Piston Displacement:

Any acceptable

Integral Reduction/reverse Gear:

Included

Outboard Drive Lubrication Method:

Forced feed

Outboard Drive Steering Mechanism Operating Method:

Steering wheel and level controlled hydraulic motor and emergency hand crank

Outboard Drive Tilting Mechanism Operating Method:

Level controlled hydraulic motor and emergency hand crank

Outboard Drive Locking Brake:

Included

Outboard Drive Protective Skeg:

Included

Propeller Blade Quantity:

3

Propeller Blade Diameter:

60.000 inches

Propeller Blade Pitch:

38.000 inches

Propeller Rotation Direction:

Clockwise

Propeller Material:

Manganese bronze

Propeller Attachment Method:

Any acceptable

Fuel Type:

Diesel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T274-a