

View Online at <https://aerobasegroup.com/nsn/2010-00-959-3011>

Inside Diameter:

Between 3.500 inches and 5.250 inches

Major Diameter:

12.500 inches

Thread Length:

11.125 inches

Width:

Between 3.250 inches and 3.312 inches

Overall Length:

56.417 feet

Outside Diameter:

20.000 inches

Taper Length:

47.000 feet

Taper Major Diameter:

20.0156 inches

Depth:

1.522 inches

Surface Finish:

Smooth machined

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber

Construction:

Hollow

Thread Quantity:

4 per inch

Usage Location:

Port or starboard

Forward End Keyway:

Not provided

After End Keyway:

Provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

32.750 inches

Forward End Coupling Length:

0.667 feet

Forward End Coupling Thickness:

4.000 inches

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

21.875 inches

Forward Bearing Sleeve Length:

7.250 feet

After Bearing Sleeve Outside Diameter:

21.875 inches

After Bearing Sleeve Length:

8.459 feet

Covering Location:

Surfaces between bearing sleeves

Taper:

1.000 per foot in inches

Material:

Steel, mil-s-23284

Material:

Steel, mil-s-23284

Quantity:

2

Reference Number Differentiating Characteristics:

As differentiated by material and specification data

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T08000