

View Online at <https://aerobasegroup.com/nsn/2010-00-990-2169>

Major Diameter:

1.250 inches

Thread Length:

1.315 inches

Width:

Between 0.437 inches and 0.438 inches

Overall Length:

6.917 feet

Outside Diameter:

1.750 inches

Taper Length:

0.417 feet

Taper Major Diameter:

1.750 inches

Keyway Width:

Between 0.437 inches and 0.438 inches

Keyway Depth:

Between 0.219 inches and 0.222 inches

Depth:

Between 0.219 inches and 0.222 inches

Keyway Quantity:

1

Surface Finish:

Smooth machined

Unit Type:

Propeller shaft section

Construction:

Solid

Thread Quantity:

7 per inch

Usage Location:

Inboard/outboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Taper Length:

0.292 feet

Threaded Forward End:

Included

Forward End Major Diameter:

0.875 inches

Forward End Thread Quantity:

14 per inch

Forward End Thread Length:

1.060 inches

After End Design:

Tapered

Threaded After End:

Included

Forward End Taper Major Diameter:

1.750 inches

Taper:

Between 0.726 per foot in inches and 0.728 per foot in inches

Forward End Taper:

Between 0.7500 per foot in inches and 0.7519 per foot in inches

Material:

Steel, corrosion resisting

Material:

Stainless steel

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000