

View Online at <https://aerobasegroup.com/nsn/2010-01-015-1534>

Major Diameter:

14.000 inches

Thread Length:

12.000 inches

Overall Length:

37.000 feet

Taper Length:

3.500 feet

Taper Major Diameter:

Between 22.998 inches and 23.000 inches

Depth:

Between 1.843 inches and 1.853 inches

Surface Finish:

Any acceptable

Furnished Items And Quantity:

Propeller nut 1, propeller key 2, pipe plug 1, plug 1

Unit Type:

Propeller shaft section

Protective Covering Type:

Rubber, synthetic

Construction:

Hollow

Thread Quantity:

4 per inch

Forward End Keyway:

Not provided

After End Keyway:

Provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

Between 37.245 inches and 37.250 inches

Forward End Coupling Thickness:

Between 4.615 inches and 4.625 inches

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

Between 24.745 inches and 24.750 inches

Forward Bearing Sleeve Length:

0.917 feet

After Bearing Sleeve Outside Diameter:

Between 24.745 inches and 24.750 inches

After Bearing Sleeve Length:

11.750 feet

Covering Location:

Surfaces between bearing sleeves

Taper:

1.000 per foot in inches

Material:

Steel, mil-s-23284, class 3

Material:

Steel, mil-s-23284, class 3

Quantity:

2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T08000