

View Online at <https://aerobasegroup.com/nsn/2010-01-021-9542>

**Major Diameter:**

1.500 inches

**Thread Length:**

2.625 inches

**Width:**

Between 0.499 inches and 0.500 inches

**Overall Length:**

9.833 feet

**Outside Diameter:**

2.000 inches

**Taper Length:**

0.479 feet

**Taper Major Diameter:**

2.000 inches

**Keyway Width:**

Between 0.499 inches and 0.500 inches

**Keyway Depth:**

Between 0.251 inches and 0.254 inches

**Depth:**

Between 0.251 inches and 0.254 inches

**Keyway Quantity:**

1

**Surface Finish:**

Any acceptable

**Unit Type:**

Propeller shaft section

**Construction:**

Solid

**Thread Quantity:**

6 per inch

**Usage Location:**

Port/starboard

**Forward End Design:**

Straight

**Forward End Diameter:**

2.000 inches

**Forward End Keyway:**

Provided

**After End Keyway:**

Provided

**Threaded Forward End:**

Not included

**After End Design:**

Tapered

**Threaded After End:**

Included

**Taper:**

0.750 per foot in inches

**Special Features:**

Keyway on aft and forward end is 4 1/4 inches min. Length. Shaft extends 1/2 inch past threaded propeller head with a 13/64 inch hole drilled for a 3/16 inch cotter pin for extra safety of locknut on aft end

**Material:**

Steel, corrosion resisting

**Material:**

Stainless steel

**Quantity:**

1

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T08000