

View Online at <https://aerobasegroup.com/nsn/2010-01-031-6094>

Major Diameter:

3.000 inches

Thread Length:

4.000 inches

Width:

Between 0.997 inches and 1.004 inches

Overall Length:

20.938 feet

Outside Diameter:

4.250 inches

Taper Length:

0.917 feet

Taper Major Diameter:

4.250 inches

Keyway Width:

Between 0.997 inches and 1.004 inches

Keyway Depth:

Between 0.373 inches and 0.376 inches

Depth:

Between 0.374 inches and 0.377 inches

Keyway Quantity:

1

Surface Finish:

Rough ground

Unit Type:

Propeller shaft section

Construction:

Solid

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Coupling Design:

Detachable

Forward End Coupling Type:

Flange

Forward End Coupling Outside Diameter:

7.000 inches

Forward End Coupling Length:

0.771 feet

Forward End Coupling Thickness:

1.000 inches

Forward End Taper Length:

0.625 feet

Threaded Forward End:

Not included

After End Design:

Tapered

Threaded After End:

Included

Forward End Taper Major Diameter:

4.250 inches

Taper:

Between 0.750 per foot in inches and 0.751 per foot in inches

Forward End Taper:

Between 0.750 per foot in inches and 0.751 per foot in inches

Material:

Steel

Material:

Steel

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T08000