

View Online at <https://aerobasegroup.com/nsn/2010-01-031-6094>

**Major Diameter:**

3.000 inches

**Thread Length:**

4.000 inches

**Width:**

Between 0.997 inches and 1.004 inches

**Overall Length:**

20.938 feet

**Outside Diameter:**

4.250 inches

**Taper Length:**

0.917 feet

**Taper Major Diameter:**

4.250 inches

**Keyway Width:**

Between 0.997 inches and 1.004 inches

**Keyway Depth:**

Between 0.373 inches and 0.376 inches

**Depth:**

Between 0.374 inches and 0.377 inches

**Keyway Quantity:**

1

**Surface Finish:**

Rough ground

**Unit Type:**

Propeller shaft section

**Construction:**

Solid

**Thread Quantity:**

4 per inch

**Usage Location:**

Port/starboard

**Forward End Design:**

Tapered

**Forward End Keyway:**

Provided

**After End Keyway:**

Provided

**Forward End Coupling Design:**

Detachable

**Forward End Coupling Type:**

Flange

**Forward End Coupling Outside Diameter:**

7.000 inches

**Forward End Coupling Length:**

0.771 feet

**Forward End Coupling Thickness:**

1.000 inches

**Forward End Taper Length:**

0.625 feet

**Threaded Forward End:**

Not included

**After End Design:**

Tapered

**Threaded After End:**

Included

**Forward End Taper Major Diameter:**

4.250 inches

**Taper:**

Between 0.750 per foot in inches and 0.751 per foot in inches

**Forward End Taper:**

Between 0.750 per foot in inches and 0.751 per foot in inches

**Material:**

Steel

**Material:**

Steel

**Quantity:**

1

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T08000