

View Online at <https://aerobasegroup.com/nsn/2010-01-032-8886>

Inside Diameter:

Between 12.500 inches and 12.516 inches

Overall Length:

36.007 feet

Outside Diameter:

Between 18.875 inches and 18.925 inches

Surface Finish:

Ground/polished

Coupling Outside Diameter:

36.000 inches

Furnished Items And Quantity:

Bolt hex. Head 12, nut hex. 12, o-ring 1, spacer 1

Unit Type:

Line shaft section

Protective Covering Type:

Composition rust preventive

Construction:

Hollow

Usage Location:

Port/starboard

Forward End Keyway:

Not provided

After End Keyway:

Not provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

33.250 inches

Forward End Coupling Length:

0.397 feet

Forward End Coupling Thickness:

3.875 inches

Threaded Forward End:

Not included

After End Coupling Design:

Integral

Coupling Length:

0.364 feet

Coupling Thickness:

4.375 inches

Threaded After End:

Not included

Forward Bearing Sleeve Outside Diameter:

Between 19.000 inches and 19.004 inches

Forward Bearing Sleeve Length:

3.333 feet

Covering Location:

All bore surfaces

Material:

Steel, mil-s-23284, class 1

Material:

Steel

Material Specification:

Mil-s-23284, class 1 military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000

Mil-std (military Standard):

Mil-s-23284 spec.