

View Online at <https://aerobasegroup.com/nsn/2010-01-090-4703>

Major Diameter:

1.750 inches

Thread Length:

3.141 inches

Width:

Between 0.623 inches and 0.6250 inches

Overall Length:

14.104 feet

Outside Diameter:

2.500 inches

Taper Length:

0.604 feet

Taper Major Diameter:

2.500 inches

Keyway Width:

Between 0.6235 inches and 0.6250 inches

Keyway Depth:

Between 0.312 inches and 0.315 inches

Depth:

Between 0.312 inches and 0.315 inches

Keyway Quantity:

1

Unit Type:

Complete shaft

Thread Quantity:

5 per inch

Usage Location:

Port or starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Coupling Design:

Detachable

Forward End Coupling Type:

Flange

Forward End Coupling Outside Diameter:

Between 10.495 inches and 10.500 inches

Forward End Coupling Length:

0.667 feet

Forward End Coupling Thickness:

6.250 inches

Forward End Taper Length:

0.459 feet

Threaded Forward End:

Not included

Forward End Major Diameter:

1.750 inches

Forward End Thread Quantity:

5 per inch

Forward End Thread Length:

1.750 inches

After End Coupling Design:

Integral

Coupling Type:

Sleeve

After End Design:

Tapered

Threaded After End:

Included

Forward End Taper Major Diameter:

2.500 inches

Taper:

0.750 per foot in inches

Forward End Taper:

0.750 per foot in inches

Material:

Corrosion-resisting steel, armco type 17-4ph, condition h-1150

Material:

Corrosion-resisting steel, armco type 17-4ph, condition h-1150

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T08000