

View Online at <https://aerobasegroup.com/nsn/2010-01-136-0655>

Major Diameter:

3.000 inches

Thread Length:

3.812 inches

Width:

Between 0.997 inches and 0.998 inches

Overall Length:

20.559 feet

Outside Diameter:

4.250 inches

Taper Length:

0.687 feet

Taper Major Diameter:

4.250 inches

Keyway Width:

Between 0.997 inches and 0.998 inches

Keyway Depth:

Between 0.309 inches and 0.312 inches

Depth:

Between 0.309 inches and 0.312 inches

Keyway Quantity:

1

Cubic Measure:

17280.000 cubic inches

Surface Finish:

Smooth machined

Intermediate Bearing Sleeve Outside Diameter:

4.750 inches

Intermediate Bearing Sleeve Length:

1.083 feet

Unit Type:

Propeller shaft section

Construction:

Solid

Unpackaged Unit Weight:

400.000 pounds

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Coupling Design:

Detachable

Forward End Coupling Type:

Flange

Forward End Coupling Outside Diameter:

11.000 inches

Forward End Coupling Length:

9.250 feet

Forward End Coupling Thickness:

1.000 inches

Forward End Taper Length:

0.500 feet

Threaded Forward End:

Included

Forward End Major Diameter:

2.500 inches

Forward End Thread Quantity:

4 per inch

Forward End Thread Length:

2.250 inches

After End Design:

Tapered

Threaded After End:

Included

Forward Bearing Sleeve Outside Diameter:

4.750 inches

Forward Bearing Sleeve Length:

1.000 feet

After Bearing Sleeve Outside Diameter:

5.000 inches

After Bearing Sleeve Length:

1.333 feet

Forward End Taper Major Diameter:

3.875 inches

Taper:

0.750 per foot in inches

Forward End Taper:

0.750 per foot in inches

Material:

Steel

Material:

Steel

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T08000