

View Online at <https://aerobasegroup.com/nsn/2010-01-136-0655>

**Major Diameter:**

3.000 inches

**Thread Length:**

3.812 inches

**Width:**

Between 0.997 inches and 0.998 inches

**Overall Length:**

20.559 feet

**Outside Diameter:**

4.250 inches

**Taper Length:**

0.687 feet

**Taper Major Diameter:**

4.250 inches

**Keyway Width:**

Between 0.997 inches and 0.998 inches

**Keyway Depth:**

Between 0.309 inches and 0.312 inches

**Depth:**

Between 0.309 inches and 0.312 inches

**Keyway Quantity:**

1

**Cubic Measure:**

17280.000 cubic inches

**Surface Finish:**

Smooth machined

**Intermediate Bearing Sleeve Outside Diameter:**

4.750 inches

**Intermediate Bearing Sleeve Length:**

1.083 feet

**Unit Type:**

Propeller shaft section

**Construction:**

Solid

**Unpackaged Unit Weight:**

400.000 pounds

**Thread Quantity:**

4 per inch

**Usage Location:**

Port/starboard

**Forward End Design:**

Tapered

**Forward End Keyway:**

Provided

**After End Keyway:**

Provided

**Forward End Coupling Design:**

Detachable

**Forward End Coupling Type:**

Flange

**Forward End Coupling Outside Diameter:**

11.000 inches

**Forward End Coupling Length:**

9.250 feet

**Forward End Coupling Thickness:**

1.000 inches

**Forward End Taper Length:**

0.500 feet

**Threaded Forward End:**

Included

**Forward End Major Diameter:**

2.500 inches

**Forward End Thread Quantity:**

4 per inch

**Forward End Thread Length:**

2.250 inches

**After End Design:**

Tapered

**Threaded After End:**

Included

**Forward Bearing Sleeve Outside Diameter:**

4.750 inches

**Forward Bearing Sleeve Length:**

1.000 feet

**After Bearing Sleeve Outside Diameter:**

5.000 inches

**After Bearing Sleeve Length:**

1.333 feet

**Forward End Taper Major Diameter:**

3.875 inches

**Taper:**

0.750 per foot in inches

**Forward End Taper:**

0.750 per foot in inches

**Material:**

Steel

**Material:**

Steel

**Quantity:**

1

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T08000