

View Online at <https://aerobasegroup.com/nsn/2010-01-141-9944>

Inside Diameter:

Between 9.000 inches and 9.001 inches

Overall Length:

34.850 feet

Outside Diameter:

18.000 inches

Diameter:

21.000 inches

Keyway Width:

3.750 inches and 3.812 inches

Keyway Depth:

1.500 inches

Keyway Quantity:

4

Cubic Measure:

739584.000 cubic inches

Surface Finish:

Ground/polished

Coupling Outside Diameter:

Between 41.245 inches and 41.250 inches

Unit Type:

Tail shaft section

Construction:

Hollow

Unpackaged Unit Weight:

31576.000 pounds

Usage Location:

Port/starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Not provided

Forward End Coupling Design:

Integral

Forward End Coupling Outside Diameter:

Between 14.372 inches and 14.374 inches

Forward End Coupling Thickness:

3.625 inches

Forward End Taper Length:

1.375 feet

Threaded Forward End:

Not included

After End Coupling Design:

Integral

Coupling Thickness:

7.250 inches

After End Design:

Straight

Threaded After End:

Not included

Forward Bearing Sleeve Outside Diameter:

Between 20.245 inches and 20.250 inches

Forward Bearing Sleeve Length:

3.000 feet

After Bearing Sleeve Outside Diameter:

Between 22.995 inches and 23.000 inches

After Bearing Sleeve Length:

5.500 feet

Forward End Taper Major Diameter:

Between 17.825 inches and 17.828 inches

Forward End Taper:

0.125 per foot in inches

Material:

Steel, mil-s-23284

Material:

Steel, mil-s-23284

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T08000