NSN 2010-01-377-2282

Ship Propulsion Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2010-01-377-2282

Major Diameter:

3.000 inches

Thread Length:

4.000 inches

Width:

Between 0.997 inches and 1.004 inches

Overall Length:

20.938 feet

Outside Diameter:

4.500 inches

Taper Length:

0.917 feet

Taper Major Diameter:

4.250 inches

Keyway Width:

Between 0.997 inches and 1.004 inches

Keyway Depth:

Between 0.373 inches and 0.376 inches

Depth:

Between 0.374 inches and 0.377 inches

Keyway Quantity:

1

End Application:

Used onboard 75 ft wlic coast guard vessels

Surface Finish:

Rough ground

Unit Type:

Propeller shaft section

Construction:

Solid

Thread Quantity:

4 per inch

Usage Location:

Port/starboard

Forward End Design:

Tapered

Forward End Keyway:

Provided

After End Keyway:

Provided

Forward End Coupling Design:

Detachable

NSN 2010-01-377-2282

Ship Propulsion Shaft - Page 2 of 2



Forward End Coupling Type: Flange Forward End Coupling Outside Diameter: 7.000 inches Forward End Coupling Length: 0.771 feet Forward End Coupling Thickness: 1.000 inches Forward End Taper Length: 0.625 feet Threaded Forward End: Not included After End Design: Tapered **Threaded After End:** Included Forward End Taper Major Diameter: 4.250 inches Taper: Between 0.750 per foot in inches and 0.751 per foot in inches Forward End Taper: Between 0.750 per foot in inches and 0.751 per foot in inches Material: Steel Material: Steel Quantity: Shelf Life: Unit Of Measure: **Demilitarization:** Fiig: T08000

1

N/a

No