

View Online at <https://aerobasegroup.com/nsn/2030-00-273-9195>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 motor controller

**Environmental Protection:**

Splashtight

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Drum Flange To Flange Distance And Location:**

34.500 inches second drum err-100

**Drum Diameter And Location:**

19.625 any acceptable meters preset

**Load Limit At Selected Speed And Drum Location:**

6650.0 pounds single speed second drum err-100 err-100

**Travel Rate Per Minute:**

80.0 feet

**Braking Method:**

Electric

**Power Requirement Rating:**

50.00 horsepower

**Drum Surface Design:**

Grooved

**Drum Designation:**

Left-hand

**Cooling Method:**

Any acceptable

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

As differentiated by starkimble electric motor, buships planno. S6301-f-3129105 and cutler-hammer controller catalog no.6962ed422, buships plan no. Lst1156-s6307-1187107

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A02800