

View Online at <https://aerobasegroup.com/nsn/2030-00-273-9195>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller

Environmental Protection:

Splashtight

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Drum Flange To Flange Distance And Location:

34.500 inches second drum err-100

Drum Diameter And Location:

19.625 any acceptable meters preset

Load Limit At Selected Speed And Drum Location:

6650.0 pounds single speed second drum err-100 err-100

Travel Rate Per Minute:

80.0 feet

Braking Method:

Electric

Power Requirement Rating:

50.00 horsepower

Drum Surface Design:

Grooved

Drum Designation:

Left-hand

Cooling Method:

Any acceptable

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by starkimble electric motor, buships planno. S6301-f-3129105 and cutler-hammer controller catalog no.6962ed422, buships plan no. Lst1156-s6307-1187107

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A02800