Marine Structural Metal Door - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2040-00-554-3528

| Opening Width: | |
|--|--|
| 26.000 inches | |
| Panel Thickness: | |
| 0.075 inches | |
| Operational Direction: | |
| Right-hand | |
| Design Type: | |
| Watertight | |
| Operation Method: | |
| Lever | |
| Opening Length: | |
| 66.000 inches | |
| Test Pressure Rating: | |
| 10 psi test pressure | |
| Quick Operating Feature: | |
| Included | |
| Opening Corner Radius: | |
| 8.828 inches | |
| Dog Quantity: | |
| 8 | |
| Dog Location: | |
| On frame | |
| Dog Type: | |
| Rotating | |
| Passing Scuttle: | |
| Not included | |
| Fixed Light: | |
| Included | |
| Distance Between Sill And Fixed Light: | |
| 47.328 inches | |
| Material: | |
| Steel, corrosion resisting | |
| Material: | |
| Stainless steel | |
| Specification Or Standard: | |
| 181, w/o hasp assembly | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| - | |
| Demilitarization: | |
| No | |
| | |

NSN 2040-00-554-3528

Marine Structural Metal Door - Page 2 of 2

Fiig: T274-u

