## NSN 2320-00-050-9006

Van Truck - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/2320-00-050-9006 **Body Material:** Aluminum alloy and wood **Cylinder Quantity:** 6 **Battery Quantity:** Wheel Quantity: **Drive Wheel Quantity: Engine/motor Manufacturer Code And Model Number:** 94012 nhc250 **Prime Mover Type:** Diesel engine **Engine Brake Horsepower:** 250.0 **Engine Horsepower Rating Speed In Rpm:** 2100.0 **Battery Voltage Rating In Volts:** 12.0 **Window Quantity:** 10 **Reverse Speed Quantity: Transmission Type:** Manual **Forward Speed Quantity: Seating Capacity:** 3 **Features Provided:** Air conditioning and electrical outlet and insulated and power steering and stabilizing jack and stabilizing jack and towing pintle hook and underwater fording system **Rated Load Capacity:** 5.00 tons **Drive Axle Location:** Front and rear

**Axle Drive Type:** Double reduction **Power Divider Unit:** Not included

Front Axle Engaging Mechanism Type:

Automatic

## NSN 2320-00-050-9006

Van Truck - Page 2 of 3



Rear Wheel Mounting Type:
Dual
Wheelbase:
215.00 inches
Front Wheel Tread Width:
74.00 inches
Rear Wheel Tread Width:
72.00 inches
Multifuel Design Feature:
Not included
Transmission Adjunct Type:
Transfer
Transmission Adjunct Speed Quantity:
2
Cab Type:
Conventional
Cab Roof Type:
Open
Brake Actuation Method:
Air and hydraulic
Cargo Area Length:
204.00 inches
Cargo Area Width:
82.00 inches
Cargo Area Height:
75.00 inches
Cargo Door Location:
Right side and left side and rear facing
Interior Electrical Outlet Voltage:
24
Body Manufacturer Code And Model Number:
19207 8736696
Chassis Manufacturer Code And Model Number:
19207 m811a2
Vehicle Curb Weight:
25800.0 pounds
Vehicle Maximum Gross Weight:
41200.00 pounds
Cab Door Quantity:
2
Special Features:
Body expansible to 160.00 in. Inside w, body equipped w/heaters, w/lifting eyes
Shelf Life:
N1/=

N/a

## NSN 2320-00-050-9006

Van Truck - Page 3 of 3



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

Yes - demil/mli

Fiig:

A37500