

View Online at <https://aerobasegroup.com/nsn/2320-00-540-3991>

**Body Material:**

Any acceptable

**Cylinder Quantity:**

6

**Battery Quantity:**

1

**Wheel Quantity:**

Any acceptable

**Drive Wheel Quantity:**

Any acceptable

**Prime Mover Type:**

Gasoline engine

**Engine Brake Horsepower:**

Any acceptable

**Engine Horsepower Rating Speed In Rpm:**

Any acceptable

**Battery Voltage Rating In Volts:**

12.0

**Reverse Speed Quantity:**

Any acceptable

**Transmission Type:**

Any acceptable

**Hinge Location:**

Any acceptable

**Stake Type:**

Lattice panel

**Seating Capacity:**

Any acceptable

**Features Provided:**

Tailgate and tarpaulin and top bows

**Rated Load Capacity:**

9.00 tons

**Drive Axle Location:**

Front or rear

**Axle Drive Type:**

Any acceptable

**Rear Wheel Mounting Type:**

Single or dual

**Wheelbase:**

Any acceptable

**Front Wheel Tread Width:**

Any acceptable

**Rear Wheel Tread Width:**

Any acceptable

**Cab Type:**

Conventional

**Cab Roof Type:**

Closed or open

**Brake Actuation Method:**

Any acceptable

**Tailgate Operation Method:**

Any acceptable

**Cargo Area Length:**

Any acceptable

**Cargo Area Width:**

Any acceptable

**Cargo Area Height:**

Any acceptable

**Body Hoist Type:**

Highlift

**Cab Door Quantity:**

Any acceptable

**Special Features:**

For use in loading heavy general cargo into aircraft and for handling vehicles palletized for aerial delivery; manually operated positive locking device for holding the lift mechanism in the extreme raised position; safety device to prevent sudden lowering of truck bed if hydraulic pressure is cut off; t.O. 36a12-5-11-1

**Specification Or Standard:**

Mc1 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A37500

**Mil-std (military Standard):**

Mil-t-62145 spec.