NSN 2320-00-695-9375



Wrecker Truck Tractor - Page 1 of 3 View Online at https://aerobasegroup.com/nsn/2320-00-695-9375 **Cylinder Quantity: Battery Quantity:** Wheel Quantity: **Drive Wheel Quantity: Engine/motor Manufacturer Code And Model Number:** 89619 endt673 **Prime Mover Type:** Diesel engine **Engine Brake Horsepower: Engine Horsepower Rating Speed In Rpm: Battery Voltage Rating In Volts:** 12.0 **Reverse Speed Quantity: Transmission Type:** Manual **Forward Speed Quantity: Maximum Load Rating:** 20000.0 pounds 1st winch **Seating Capacity: Features Provided:** Outrigger and towing pintle hook and trailer brake connection and underwater fording system Fifth Wheel Type: Lower fifth wheel coupler **Boom Operation Method:** Power **Gypsy Head:** Not included

Trailer Brake Connection Type: Air **Rated Load Capacity:** 5.00 tons **Drive Axle Location:** Front and rear

NSN 2320-00-695-9375 Wrecker Truck Tractor - Page 2 of 3



Axle Drive Type:
Double reduction
Power Divider Unit:
Included
Front Axle Engaging Mechanism Type:
Automatic
Rear Wheel Mounting Type:
Dual
Wheelbase:
215.00 inches
Front Wheel Tread Width:
73.62 inches
Rear Wheel Tread Width:
72.00 inches
Multifuel Design Feature:
Not included
Transmission Adjunct Type:
Transfer
Transmission Adjunct Speed Quantity:
2
Winch Location:
Front
Winch Type:
Single drum
Single drum
Boom Type:
-
Boom Type: Single telescoping
Boom Type:
Boom Type: Single telescoping Boom Maximum Length:
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction:
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction:
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type:
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type: Hydraulic
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type: Hydraulic Load Lifting Capacity Rating:
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type: Hydraulic Load Lifting Capacity Rating: 20000.0 pounds
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type: Hydraulic Load Lifting Capacity Rating: 20000.0 pounds Load Lifting Method:
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type: Hydraulic Load Lifting Capacity Rating: 20000.0 pounds Load Lifting Method: Power
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type: Hydraulic Load Lifting Capacity Rating: 20000.0 pounds Load Lifting Method: Power Cab Type:
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type: Hydraulic Load Lifting Capacity Rating: 20000.0 pounds Load Lifting Method: Power Cab Type: Conventional
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type: Hydraulic Load Lifting Capacity Rating: 20000.0 pounds Load Lifting Method: Power Cab Type: Conventional Cab Roof Type:
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type: Hydraulic Load Lifting Capacity Rating: 20000.0 pounds Load Lifting Method: Power Cab Type: Conventional Cab Roof Type: Open
Boom Type: Single telescoping Boom Maximum Length: 312.00 inches Boom Operational Direction: Rotating Minimum Swing Angle In Deg: 270.0 Crane Operation Type: Hydraulic Load Lifting Capacity Rating: 20000.0 pounds Load Lifting Method: Power Cab Type: Conventional Cab Roof Type:

NSN 2320-00-695-9375 Wrecker Truck Tractor - Page 3 of 3



Fifth Wheel Center To Cab Distance:
132.000 inches
Chassis Manufacturer Code And Model Number:
19207 m63a1c
Vehicle Curb Weight:
32830.0 pounds
Vehicle Maximum Gross Weight:
49180.00 pounds
Cab Door Quantity:
2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A37500