NSN 2320-00-702-3537

Cargo Truck - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2320-00-702-3537 **Body Material:** Steel **Cylinder Quantity:** Any acceptable **Battery Quantity:** Wheel Quantity: **Drive Wheel Quantity:** 2 **Prime Mover Type:** Gasoline engine **Engine Brake Horsepower:** Any acceptable **Engine Horsepower Rating Speed In Rpm:** Any acceptable **Battery Voltage Rating In Volts:** 12.0 **Reverse Speed Quantity:** Any acceptable **Transmission Type:** Any acceptable **Forward Speed Quantity Per Range:** Any acceptable **Forward Speed Quantity:** Any acceptable **Hinge Location: Bottom** Stake Type: Lattice panel **Seating Capacity: Features Provided:** Body crew compartment and tailgate and towing pintle hook and cab protector **Rated Load Capacity:** 2.50 tons **Drive Axle Location:** Rear **Axle Drive Type:** Conventional

Axle Speed Quantity:Any acceptable

NSN 2320-00-702-3537

Cargo Truck - Page 2 of 2



Rear Wheel Mounting Type:
Dual
Wheelbase:
Any acceptable
Front Wheel Tread Width:
Any acceptable
Rear Wheel Tread Width:
Any acceptable
Forward Speed Range Quantity:
Any acceptable
Cab Type:
Crew
Cab Roof Type:
Closed
Brake Actuation Method:
Hydraulic and vacuum
Tailgate Operation Method:
Manual
Cargo Area Length:
144.00 inches
Cargo Area Width:
80.00 inches
Cargo Area Height:
24.00 inches
Cab Door Quantity:
Any acceptable
Specification Or Standard:
15 type and c class and 1 group
Departure From Cited Document:
As modified by body interior dimensions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A37500
Mil-std (military Standard):
Mil-t-62319 spec.