NSN 2320-00-706-5348

Dump Truck - Page 1 of 2

Manual



View Online at https://aerobasegroup.com/nsn/2320-00-706-5348

| Cylinder Quantity: 6 Battery Quantity: 1 Wheel Quantity: 4 Drive Wheel Quantity: 4 Prime Mover Type: Gasoline engine Engine Brake Horsepower: Any acceptable Engine Horsepower Rating Speed In Rpm: Any acceptable Engine Horsepower Rating Speed In Rpm: Any acceptable Engine Brake Horsepower: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: 1 | Sulin dan Ouanattu. |
|--|---------------------|
| Battery Quantity: 1 Wheel Quantity: 4 Drive Wheel Quantity: 4 Prime Mover Type: Gasoline engine Engine Brake Horsepower: Any acceptable Engine Horsepower Rating Speed In Rpm: Any acceptable Battery Voltage Rating In Volts: 12.0 Reverse Speed Quantity: 1 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Akle Location: Front and rear Akle Drive Type: Conventional Akle Speed Quantity: | |
| 1 Wheel Quantity: 4 Very Wheel Quantity: 4 Prime Mover Type: Gasoline engine Engine Brake Horsepower: Any acceptable Engine Horsepower Rating Speed In Rpm: Any acceptable Battery Voltage Rating In Volts: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection: 5.00 tons Drive Akle Location: Front and rear Akle Drive Type: Conventional Akle Speed Quantity: | |
| Wheel Quantity: 4 Drive Wheel Quantity: 4 Frime Mover Type: Gasoline engine Engine Brake Horsepower: Any acceptable Engine Horsepower Rating Speed In Rpm: Any acceptable Engine Horsepower Rating In Volts: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Titting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chuie opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tos Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| 4 Prime Mover Type: Gasoline engine Engine Brake Horsepower: Any acceptable Engine Horsepower Rating Speed In Rpm: Any acceptable Engine Voltage Rating In Volts: 12.0 Reserves Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Features Included or not included Seating Capacity: Any acceptable Foatures Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tos Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Drive Wheel Quantity: 4 Prime Mover Type: Gasoline engine Engine Brake Horsepower: Any acceptable Engine Horsepower Rating Speed In Rpm: Any acceptable Battery Voltage Rating In Volts: 12.0 Reverse Speed Quantity: 17 Insmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provide: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Ali Rated Load Capacity: 5.00 tos Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| 4 Prime Mover Type: Gasoline engine Engine Brake Horsepower: Any acceptable Engine Horsepower Rating Speed in Rpm: Any acceptable Battery Voltage Rating in Volts: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilling Feature: Included or not included Seating Capacity: Any acceptable Features Providea: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: AIr Rated Load Capacity: Aloute Opening and tailgate and tarpaulin and top Lows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: AIr Rated Load Capacity: Aloute Opening and tailgate and tarpaulin and top Lows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: AIr Rated Load Capacity: Aloute Opening and tailgate and tarpaulin and top Lows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: AIr Rated Load Capacity: Aloute Opening and tailgate and tarpaulin and top Lows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: AIR Akel Drive Ayle Location: Front and rear Akel Drive Type: Conventional Akel Speed Quantity: | |
| Prime Mover Type: Gasoline engine Engine Brake Horsepower: Any acceptable Engine Horsepower Rating Speed In Rpm: Any acceptable Battery Voltage Rating In Volts: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Traller Brake Connection Type: Air Rated Locad Capacity: 5.00 tons Drive Axile Location: Front and rear Axile Drive Type: Conventional Axile Speed Quantity: | |
| Gasoline engine Engine Brake Horsepower: Any acceptable Engine Horsepower Rating Speed In Rpm: Any acceptable Battery Voltage Rating In Volts: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Stottim and top Stottim and top Stottim Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Engine Brake Horsepower. Any acceptable Engine Horsepower Ratting Speed In Rpm: Any acceptable Battery Voltage Ratting In Volts: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chate opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Ratel Load Capacity: Any ackel Location: Chate opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Ratel Load Capacity: Chote opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Ratel Load Capacity: Chote Akle Location: Chote opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Ratel Load Capacity: Chote Akle Location: Chote opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Akle Location: Chote opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Akle Location: Chote opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Akle Drive Type: Chote opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Akle Drive Type: Air Akle Drive Type: Air Akle Drive Akle Location: Air Akle Drive Type: Air Akl | |
| Any acceptable Engine Horsepower Rating Speed In Rpm: Any acceptable Battery Voltage Rating In Volts: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and taligate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Ali Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Engine Forsepower Rating Speed In Rpm: Any acceptable Battery Voltage Rating In Volts: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and taligate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Any acceptable Battery Voltage Rating In Volts: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Battery Voltage Rating In Volts: 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| 12.0 Reverse Speed Quantity: 1 Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Reverse Speed Quantity: Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Transmission Type: Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Manual Forward Speed Quantity: 10 Hinge Location: Bottom and top Titting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Forward Speed Quantity: 10 Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Hinge Location: Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Bottom and top Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Tilting Feature: Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Included or not included Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Seating Capacity: Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | - |
| Any acceptable Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Features Provided: Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Chute opening and tailgate and tarpaulin and top bows and towing pintle hook and trailer brake connection and cab protector Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Trailer Brake Connection Type: Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Air Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Rated Load Capacity: 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| 5.00 tons Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Front and rear Axle Drive Type: Conventional Axle Speed Quantity: | |
| Axle Drive Type: Conventional Axle Speed Quantity: | |
| Conventional Axle Speed Quantity: | |
| Axle Speed Quantity: | |
| | |
| | |
| Front Axle Engaging Mechanism Type: | |

NSN 2320-00-706-5348 Dump Truck - Page 2 of 2



| Rear Wheel Mounting Type: |
|---|
| Dual |
| Wheelbase: |
| Any acceptable |
| Front Wheel Tread Width: |
| Any acceptable |
| Rear Wheel Tread Width: |
| Any acceptable |
| Transmission Adjunct Type: |
| Transfer and overdrive |
| Transmission Adjunct Speed Quantity: |
| 2 |
| Cab Type: |
| Conventional or over engine |
| Cab Roof Type: |
| Closed |
| Brake Actuation Method: |
| Air and hydraulic |
| Tailgate Operation Method: |
| Any acceptable |
| Cargo Area Length: |
| 96.00 inches |
| |
| Cargo Area Width: |
| Cargo Area Width: 78.00 inches |
| _ |
| 78.00 inches |
| 78.00 inches Cargo Area Height: |
| 78.00 inches Cargo Area Height: Any acceptable |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: Tilt and highlift |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: Tilt and highlift Cab Door Quantity: |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: Tilt and highlift Cab Door Quantity: 2 |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: Tilt and highlift Cab Door Quantity: 2 Specification Or Standard: |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: Tilt and highlift Cab Door Quantity: 2 Specification Or Standard: 3 type and d class |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: Tilt and highlift Cab Door Quantity: 2 Specification Or Standard: 3 type and d class Shelf Life: |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: Tilt and highlift Cab Door Quantity: 2 Specification Or Standard: 3 type and d class Shelf Life: N/a |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: Tilt and highlift Cab Door Quantity: 2 Specification Or Standard: 3 type and d class Shelf Life: N/a Unit Of Measure: |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: Tilt and highlift Cab Door Quantity: 2 Specification Or Standard: 3 type and d class Shelf Life: N/a Unit Of Measure: |
| 78.00 inches Cargo Area Height: Any acceptable Side Removability: Nonremovable Err Default: Err default Body Hoist Type: Tilt and highlift Cab Door Quantity: 2 Specification Or Standard: 3 type and d class Shelf Life: N/a Unit Of Measure: Demilitarization: |