

View Online at <https://aerobasegroup.com/nsn/2320-00-835-8639>

Cylinder Quantity:

6

Battery Quantity:

2

Wheel Quantity:

6

Drive Wheel Quantity:

6

Engine/motor Manufacturer Code And Model Number:

02978 r6602

Prime Mover Type:

Gasoline engine

Engine Brake Horsepower:

224.0

Engine Horsepower Rating Speed In Rpm:

2800.0

Battery Voltage Rating In Volts:

12.0

Reverse Speed Quantity:

1

Transmission Type:

Manual

Forward Speed Quantity:

5

Maximum Load Rating:

20000.0 pounds 1st winch

Seating Capacity:

3

Features Provided:

Outrigger and power steering and towing pintle hook and trailer brake connection and underwater fording system

Fifth Wheel Type:

Lower fifth wheel coupler

Boom Operation Method:

Power

Gypsy Head:

Not included

Trailer Brake Connection Type:

Air

Rated Load Capacity:

5.00 tons

Drive Axle Location:

Front and rear

Axle Drive Type:

Double reduction

Power Divider Unit:

Not included

Front Axle Engaging Mechanism Type:

Automatic

Rear Wheel Mounting Type:

Dual

Wheelbase:

215.00 inches

Front Wheel Tread Width:

74.00 inches

Rear Wheel Tread Width:

72.00 inches

Transmission Adjunct Type:

Transfer

Transmission Adjunct Speed Quantity:

2

Winch Location:

Front

Winch Type:

Single drum

Boom Type:

Single telescoping

Boom Maximum Length:

312.00 inches

Boom Operational Direction:

Rotating

Minimum Swing Angle In Deg:

270.0

Crane Operation Type:

Hydraulic

Load Lifting Capacity Rating:

20000.0 pounds

Load Lifting Method:

Power

Cab Type:

Conventional

Cab Roof Type:

Open

Brake Actuation Method:

Air and hydraulic

Fifth Wheel Center To Cab Distance:

132.000 inches

Chassis Manufacturer Code And Model Number:

19207 m63c

Vehicle Curb Weight:

32830.0 pounds

Cab Door Quantity:

2

Specification Or Standard:

Group 1 and model m246

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A37500