NSN 2320-00-892-1964

Dump Truck - Page 1 of 2

Any acceptable



View Online at https://aerobasegroup.com/nsn/2320-00-892-1964

Cylinder Quantity:
Any acceptable
Battery Quantity:
1
Wheel Quantity:
4
Drive Wheel Quantity:
4
Prime Mover Type:
Gasoline engine
Engine Brake Horsepower:
Any acceptable
Battery Voltage Rating In Volts:
12.0
Reverse Speed Quantity:
Any acceptable
Transmission Type:
Any acceptable
Hinge Location:
Bottom and top
Seating Capacity:
3
3 Features Provided:
Features Provided:
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity:
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location:
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear Axle Drive Type:
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear Axle Drive Type: Conventional
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity:
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: Any acceptable
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: Any acceptable Front Axle Engaging Mechanism Type:
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: Any acceptable Front Axle Engaging Mechanism Type: Automatic
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: Any acceptable Front Axle Engaging Mechanism Type: Automatic Rear Wheel Mounting Type:
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: Any acceptable Front Axle Engaging Mechanism Type: Automatic Rear Wheel Mounting Type: Dual
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: Any acceptable Front Axle Engaging Mechanism Type: Automatic Rear Wheel Mounting Type: Dual Wheelbase:
Features Provided: Cab protector and hoist locking device and tailgate and towing pintle hook Rated Load Capacity: Any acceptable Drive Axle Location: Front and rear Axle Drive Type: Conventional Axle Speed Quantity: Any acceptable Front Axle Engaging Mechanism Type: Automatic Rear Wheel Mounting Type: Dual Wheelbase: Any acceptable

NSN 2320-00-892-1964Dump Truck - Page 2 of 2



Transmission Adjunct Type:
Any acceptable
Winch Location:
Any acceptable
Cab Type:
Conventional
Cab Roof Type:
Closed
Brake Actuation Method:
Any acceptable
Tailgate Operation Method:
Manual
Cargo Area Length:
144.00 inches
Cargo Area Width:
90.00 inches
Cargo Area Height:
Any acceptable
Side Removability:
Removable
Err Default:
Err default
Body Hoist Type:
Tilt
Cab Door Quantity:
2
Functional Description:
Base maintenance
Specification Or Standard:
13 type and e class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A37500