NSN 2320-00-892-5462

Wrecker Truck - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2320-00-892-5462

| Cylinder Quantity: |
|--|
| 8 |
| |
| Battery Quantity: |
| Wheel Quantity: |
| 4 |
| Drive Wheel Quantity: |
| 2 |
| Prime Mover Type: |
| Gasoline engine |
| Engine Brake Horsepower: |
| 160.0 |
| Engine Horsepower Rating Speed In Rpm: |
| 4000.0 |
| Battery Voltage Rating In Volts: |
| 12.0 |
| Reverse Speed Quantity: |
| 1 |
| Transmission Type: |
| Manual |
| Forward Speed Quantity: |
| 5 |
| Maximum Load Rating: |
| 20000.0 pounds |
| Seating Capacity: |
| 3 |
| Features Provided: |
| Outrigger |
| Boom Operation Method: |
| Power |
| Gypsy Head: |
| Not included |
| Rated Load Capacity: |
| 3.00 tons |
| Drive Axle Location: |
| Rear |
| Axle Drive Type: |
| Conventional |
| Axle Speed Quantity: |
| 1 |
| Rear Wheel Mounting Type: |

Dual

NSN 2320-00-892-5462 Wrecker Truck - Page 2 of 2



| Wheelbase: |
|--|
| 174.00 inches |
| Front Wheel Tread Width: |
| 69.54 inches |
| Rear Wheel Tread Width: |
| 69.50 inches |
| Winch Location: |
| Behind cab |
| Winch Type: |
| Double drum |
| Boom Type: |
| Double fixed |
| Boom Maximum Length: |
| Any acceptable |
| Boom Operational Direction: |
| Elevating and rotating |
| Minimum Swing Angle In Deg: |
| 120.0 |
| Load Lifting Capacity Rating: |
| 20000.0 pounds |
| Load Lifting Method: |
| Power |
| Cab Type: |
| Conventional |
| Cab Roof Type: |
| Closed |
| Brake Actuation Method: |
| Hydraulic and vacuum |
| Cab Door Quantity: |
| 2 |
| Specification Or Standard: |
| V type |
| Reference Number Differentiating Characteristics: |
| As differentiated by item name and year model 1962 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A37500 |